INDUSTRIAL OIL

Commercial Chassis Grease

Everyday chassis lubrication

NLGI Grade 2 chassis grease

PRODUCT DESCRIPTION

Motoforce Commercial Chassis Grease is a chassis grease for routine servicing of commercial vehicle lubrication points. Supplied in 18 kg and 180 kg packs for workshops handling regular fleet maintenance.

APPLICATIONS

- Fleet Servicing
- Chassis Lubrication Points
- Commercial Vehicles

SPECIFICATIONS

- NLGI Grade 2 chassis grease

PACK SIZES

18kg 180kg

FEATURES & BENEFITS

- Economical grease for routine servicing of commercial vehicle chassis points.
- Good adhesion and water resistance.
- Protects pins and bushes against wear and rust.
- Supplied in bulk packs for fleet maintenance.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
NLGI Consistency Grade	—	—	2
Thickener Type	—	—	Lithium soap
Worked Penetration @ 25 °C (60 strokes)	ASTM D217	0.1 mm	265 – 295
Dropping Point	ASTM D566	°C	≥ 170
Base Oil Viscosity @ 40 °C	ASTM D445	cSt	110

RECOMMENDATIONS

- Grease chassis points at the interval in the vehicle service schedule — more often in wet or dusty conditions.
- Purge old grease until fresh grease appears at the joint.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.