MOTORCYCLE ENGINE OIL

Eco 4T 20W-40

Economical 4T for daily commute

SAE 20W-40 | API SL | JASO MA2

PRODUCT DESCRIPTION

Eco 4T 20W-40 delivers reliable everyday performance and engine protection for commuter motorcycles, with API SL grade and JASO MA2 clutch compatibility.

APPLICATIONS

- Commuter Bikes
- Budget Motorcycles

SPECIFICATIONS

- API SL
- JASO MA2

PACK SIZES

900ml | 1L | 20L | 50L | 210L

FEATURES & BENEFITS

- Economical API SL protection for daily commuting.
- JASO MA2 clutch compatibility for smooth, slip-free riding.
- Better oxidation stability than older API SJ oils.
- Helps keep the engine clean and running smoothly.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Density @ 15 °C	ASTM D4052	g/cm³	**0.884**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**123**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**14.6**
Viscosity Index	ASTM D2270	—	**120**
Flash Point (COC)	ASTM D92	°C	**220**
Pour Point	ASTM D97	°C	**-21**
Total Base Number	ASTM D2896	mg KOH/g	**7**
Sulphated Ash	ASTM D874	% wt	**0.85**

RECOMMENDATIONS

- Follow the motorcycle manufacturer's recommended oil change interval.
- Fill to the level marked on the dipstick or sight glass — do not overfill.
- Not recommended for use in 2-stroke engines.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.