HEAVY DUTY DIESEL ENGINE OIL

Endura 15W-40

Heavy-duty diesel — API CI-4 Plus

SAE 15W-40 | API CI-4 Plus

PRODUCT DESCRIPTION

Endura 15W-40 is a premium heavy-duty diesel engine oil meeting API CI-4 Plus specification. Provides outstanding soot dispersion, wear protection and oxidation stability for modern Tier-3 diesel engines under extreme operating conditions.

APPLICATIONS

- Trucks
- Buses
- Off-Road Diesel
- Tractors
- Construction Equipment

SPECIFICATIONS

- API CI-4 Plus

PACK SIZES

7L | 7.5L | 10L | 15L | 20L | 26L | 50L | 210L

FEATURES & BENEFITS

- Excellent soot dispersancy controls viscosity increase in EGR-equipped engines.
- High TBN neutralises combustion acids for long drain intervals.
- Outstanding wear protection for liners, rings and valve train.
- Shear-stable 15W-40 grade holds viscosity under severe load.
- Suitable for mixed fleets of trucks, buses, tractors and construction equipment.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Density @ 15 °C	ASTM D4052	g/cm^3	**0.882**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**110**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**14.8**
Viscosity Index	ASTM D2270	—	**138**
Flash Point (COC)	ASTM D92	°C	**226**
Pour Point	ASTM D97	°C	**-27**
Total Base Number	ASTM D2896	mg KOH/g	**10**
Sulphated Ash	ASTM D874	% wt	**1.35**

RECOMMENDATIONS

- Follow the vehicle manufacturer's recommended drain interval and viscosity grade.
- Do not mix with other oils; when switching, drain fully and change the oil filter.
- Check the oil level regularly and top up with the same grade.
- Base drain intervals on OEM guidance and oil analysis for severe-duty fleets.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.