PASSENGER CAR ENGINE OIL

Eurotech 20W-50

Multi-grade for petrol & diesel

SAE 20W-50 | API SG | API CF

PRODUCT DESCRIPTION

Eurotech 20W-50 is a high-quality multi-grade engine oil with carefully balanced additives offering reliable wear protection, oxidation stability and deposit control for petrol and diesel passenger vehicles in hot climates.

APPLICATIONS

- Older Petrol Cars
- Diesel Vehicles
- Tropical Climate Use

SPECIFICATIONS

- API SG
- API CF

PACK SIZES

1L | 3L | 3.5L | 50L | 210L

FEATURES & BENEFITS

- Thick 20W-50 oil film suits older and high-mileage engines with worn clearances.
- Helps reduce oil consumption and blow-by in older engines.
- Balanced additive system protects petrol and diesel engines alike.
- High viscosity holds up in hot tropical conditions.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Density @ 15 °C	ASTM D4052	g/cm³	**0.889**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**165**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**18.6**
Viscosity Index	ASTM D2270	—	**124**
Flash Point (COC)	ASTM D92	°C	**226**
Pour Point	ASTM D97	°C	**-21**
Total Base Number	ASTM D2896	mg KOH/g	**7.5**
Sulphated Ash	ASTM D874	% wt	**0.9**

RECOMMENDATIONS

- Follow the vehicle manufacturer's recommended drain interval and viscosity grade.
- Do not mix with other oils; when switching, drain fully and change the oil filter.
- Check the oil level regularly and top up with the same grade.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.