INDUSTRIAL OIL

Premium Chassis Grease

Bulk chassis lubrication

NLGI Grade 2 chassis grease

PRODUCT DESCRIPTION

Motoforce Premium Chassis Grease is intended for chassis lubrication points — kingpins, shackle pins, spring bushes and steering linkages on commercial vehicles. Supplied in 18 kg and 180 kg packs for workshop and fleet-scale use.

APPLICATIONS

- Commercial Vehicle Chassis
- Kingpins & Shackle Pins
- Steering Linkages

SPECIFICATIONS

- NLGI Grade 2 chassis grease

PACK SIZES

18kg 180kg

FEATURES & BENEFITS

- Tacky formulation clings to kingpins, shackle pins and spring bushes.
- Resists water washout from road splash.
- Rust and corrosion protection for exposed chassis points.
- Supplied in bulk packs for workshop and fleet use.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
NLGI Consistency Grade	—	—	2
Thickener Type	—	—	Lithium soap
Worked Penetration @ 25 °C (60 strokes)	ASTM D217	0.1 mm	265 – 295
Dropping Point	ASTM D566	°C	≥ 180
Base Oil Viscosity @ 40 °C	ASTM D445	cSt	150
Water Washout @ 79 °C	ASTM D1264	% wt	≤ 8

RECOMMENDATIONS

- Grease chassis points at the interval in the vehicle service schedule — more often in wet or dusty conditions.
- Purge old grease until fresh grease appears at the joint.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.