PUMP SET & SPECIALTY

Marshal Pump Set 20W-40

Built for agricultural pump sets

SAE 20W-40 | Pump-set / stationary diesel engine oil

PRODUCT DESCRIPTION

Marshal Pump Set 20W-40 is engineered for the continuous-duty demands of agricultural pump sets, generators and small stationary diesel engines.

APPLICATIONS

- Agricultural Pump Sets
- Small Diesel Engines
- Generators

SPECIFICATIONS

- Pump-set / stationary diesel engine oil

PACK SIZES

1.5L | 3.5L

FEATURES & BENEFITS

- Formulated for long, continuous running hours of agricultural pump sets.
- Anti-wear protection for small, heavily loaded diesel engines.
- Oxidation resistance controls thickening in hot, dusty conditions.
- Rust and corrosion protection during long idle periods between seasons.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Density @ 15 °C	ASTM D4052	g/cm³	**0.885**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**125**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**14.5**
Viscosity Index	ASTM D2270	—	**118**
Flash Point (COC)	ASTM D92	°C	**218**
Pour Point	ASTM D97	°C	**-21**
Total Base Number	ASTM D2896	mg KOH/g	**6**
Sulphated Ash	ASTM D874	% wt	**0.8**

RECOMMENDATIONS

- Change oil at the interval recommended by the pump-set manufacturer, typically every 200–250 running hours.
- Keep the air filter clean to prevent dust contamination of the oil.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.