TRANSMISSION & TRACTOR OILS

TQ Sigma

Premium torque-converter & transmission fluid

Premium ATF / torque-converter fluid

PRODUCT DESCRIPTION

TQ Sigma is a premium quality torque-converter and automatic transmission fluid engineered for smooth shifting, anti-shudder performance and oxidation stability across a wide temperature range.

APPLICATIONS

- Automatic Transmissions
- Torque Converters
- Hydraulic Systems

SPECIFICATIONS

- Premium ATF / torque-converter fluid

PACK SIZES

500ml · 1L · 5L · 10L · 15L · 20L · 26L · 50L · 210L

FEATURES & BENEFITS

- Stable friction properties give smooth, consistent shifts.
- Anti-shudder performance in torque-converter lock-up clutches.
- High viscosity index keeps it fluid in the cold and protective when hot.
- Oxidation resistance for long fluid life; also suitable for power steering.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Colour	Visual	—	**Red**
Density @ 15 °C	ASTM D4052	g/cm³	**0.862**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**35.5**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**7.3**
Viscosity Index	ASTM D2270	—	**175**
Flash Point (COC)	ASTM D92	°C	**196**
Pour Point	ASTM D97	°C	**-42**

RECOMMENDATIONS

- Use where the manufacturer specifies a conventional mineral ATF. Do not use in CVTs or DCTs unless specifically approved.
- Do not mix with other transmission fluids.
- Check fluid level with the engine running and transmission warm, as per the vehicle manual.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.