TRANSMISSION & TRACTOR OILS

Wet Brake UTTO

Universal Tractor Transmission Oil

API GL-4 | UTTO

PRODUCT DESCRIPTION

Wet Brake UTTO is a universal tractor transmission oil designed for tractor transmissions, hydraulics, PTO and wet-brake systems — a true single-fluid solution for modern tractors.

APPLICATIONS

- Tractors
- Wet-Brake Systems
- Hydraulics
- PTO Systems

SPECIFICATIONS

- API GL-4
- UTTO

PACK SIZES

1L | 5L | 10L | 20L | 26L | 50L | 210L

FEATURES & BENEFITS

- One fluid for transmission, final drive, hydraulics, PTO and wet brakes.
- Friction modifiers suppress wet-brake chatter and noise.
- Anti-wear protection for hydraulic pumps and gears.
- Water tolerance and rust protection for field conditions.

TYPICAL PROPERTIES

Property	Test Method	Unit	Typical Value
Density @ 15 °C	ASTM D4052	g/cm³	**0.880**
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	**60**
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	**9.5**
Viscosity Index	ASTM D2270	—	**140**
Flash Point (COC)	ASTM D92	°C	**210**
Pour Point	ASTM D97	°C	**-33**
Copper Strip Corrosion (3 h @ 121 °C)	ASTM D130	Rating	**1b**

RECOMMENDATIONS

- Use in tractors and agricultural equipment specifying a UTTO / wet-brake fluid.
- Not for use as an engine oil.
- Drain and refill at the interval recommended by the tractor manufacturer.

HEALTH, SAFETY & STORAGE

Store sealed in a cool, dry, covered place away from sunlight and ignition sources. Avoid prolonged skin contact. Dispose of used product and containers only through an authorised collector — never into drains or soil. See the MSDS for full health and safety information.

The typical values above are obtained under normal production conditions and do not constitute a specification. Minor variations that do not affect product performance are to be expected. Motoforce Lubricants reserves the right to modify products and this information without notice. For the latest version, visit motoforcelub.com or contact us.